

- Accurate DC measurement
- High frequency response
- High shock protection
- Low noise – high resolution
- Differential-ended output signal
- Gas damping



- Structural monitoring and testing
- Aerospace vibration testing
- Automotive ride quality & comfort
- Railway engineering
- GVT and flutter testing




## Specifications:

		3002DE	3004DE	3008DE	3010DE	3020DE	3040DE	3050DE	3100DE	3200DE	3500DE
Full-scale acceleration	(g)	± 2	± 4	± 8	± 10	± 20	± 40	± 50	± 100	± 200	± 500
Frequency range (±3dB)	(Hz)	1,500	1,500	1,500	1,500	1,500	1,500	3,000	3,000	3,000	3,000
Non-linearity (full scale)	(%)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Noise (in band)	(µg/√Hz)	20	40	80	80	160	320	25	30	45	125
Scale factor (nominal)	(mV/g)	400	200	100	80	40	20	40	20	10	4
Shock survivability	(g)	5,000	5,000	5,000	5,000	5,000	5,000	6,000	6,000	6,000	6,000

## Physical and Environmental

Protection Level	IP 68
Operating Voltage	6 V – 20 V
Operating Temperature	-40 °C to +100 °C
Weight (without cable)	17 g (aluminum) 43.5 g (steel)
Housing Material	Aluminum or Steel
Connector (Optional)	D-Sub 9 or 15 pin, Lemo, Binder
Mounting	Adhesive or screw mount
Base plate (Optional)	Aluminum or Steel

## Technical Drawings:



## Options:

- Custom Cable Length
- Custom Housing Material
- Custom Connector
- Base plate